LIGHTING
LED FLOODLIGHTS



VELOCITY SERIES

Designed for performance, reliability and ease of installation, the Velocity Floodlight is a perfect option for commercial applications. Its high efficacy of 130 lumens per watt delivers optimum performance, complemented by its diffused lens and adjustable bracket which enables easy installation across a range of applications.

With an IP65 rating and tolerance across a wide ambient temperature range, the Velocity Series is built to last.

FEATURES

- User friendly driver compartment and large 6mm terminal block
- 2x25mm and 2x20mm conduit entries
- Ease of installation (no bracket removal required and hinge lid to terminal block)
- Supply cut-off to driver when lid is opened
- High efficacy
- IP65 rating

SPECIFICATIONS

POWER FACTOR	>0.9
CRI	>80
BEAM ANGLE	110°
IP RATING	65
LIFETIME (L_{70})	>70,000h
WARRANTY	5 Years

MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LUMENS	EFFICACY
EP-VEL-70	5000K	340x100x495mm	70	69.81	9279	133lm/W
EP-VEL-100	5000K	340x100x495mm	100	99.32	13070	132lm/W
EP-VEL-120	5000K	340x100x495mm	120	120	15580	130lm/W
EP-VEL-150	5000K	340x100x495mm	150	149	18497	124lm/W
EP-VEL-200	5000K	380x100x555mm	200	200.1	26821	134lm/W

VEET Approved VIC | ESS Approved NSW | EEIS Approved ACT | REES Approved SA